

Product Data Sheet

AEL 384 Grease

Description: AEL 384 Grease is a heavy-duty, multi-purpose graphite grease particularly

useful in aluminum extrusion operations. Typically used in various applications such as lubrication of extrusion dies, die assemblies, dummy blocks, shear

blades, and hot billet ends.

Typical NLGI Grade : 3.5
Properties: Graphite : 10%

Thickener : Sodium
Penetration (@77°F) : 195 - 235
Dropping Point : 360°F
Color : Black

Shelf Life : 1 year from ship date

Method of Use: AEL 384 Grease is not guaranteed to be compatible with other greases-

thoroughly remove old grease before using It can be swabbed on various surfaces that require lubrication. Consistency makes it an ideal working grease

for various metallurgical applications.

Precautions: The customary safeguards employed when storing, handling and application

should be employed. To prevent contamination, container should be sealed when not in use. Please refer to Material Safety Data Sheet for proper first aid

instructions.

Container Size: 35 lb pails or 100 lb drums



ASBURY GRAPHITE MILLS, INC.

www.asbury.com

405 Old Main Street • PO Box 144 • Asbury, New Jersey 08802 Phone: 908.537.2155 • Fax: 908.537.2908

Sales Manager: Russell Werkheiser russellw@asbury.com rev 6-1-15